



alpha® card
the telephone for chip cards





alpha® card

the telephone for chip cards



Whether in a cafe or a restaurant, in a club or a company canteen, in a shopping centre or a laundry: A telephone is standard service nowadays.

Card-operated telephones reduce the risk of vandalism and fraud.

- Use with prepaid chip cards
- No more troublesome searching for suitable coins
- Free choice of tariff; you set the amount per unit and therewith make a profitable investment of your service
- Rugged housing for wall mounting in semi-supervised locations
- Easy programming by the operator

Furthermore, lots of extras like processing of block tariffs, internal recording of takings, integrated automatic failure detection, remote reporting and a lot more.

For self-production of chip cards, the alpha® card-card manager and the appropriate chip cards as well as a PC are required.

Technical data

- Robust metal casing
- Large alphanumeric display
- Different languages can be chosen by the user
- Exact charging via metering pulse
- Payment via prepaid chip cards
- Local, short-, long-distance and worldwide calls are possible
- One freely programmable fast dialling key, e.g. for taxi
- The emergency call numbers are obtainable without chip card
- The following settings can be made:
 - Amount for the first unit
 - Amount for the subsequent unit
- Processing of metering pulse groups (block tariffing)
- Certain call numbers or numbers starting with particular digits can be programmed for special handling
- All programmed call numbers can be changed or deleted
- Payphone Recognition Tone (ID tone)
- Automatic switching to DTMF dialling during a call via * and #
- Display of minimum amount and remaining credit
- Visual and audible signal before credits are exhausted
- Last-number redialling
- The alpha® card can be called (can be deactivated)
- Automatic public line access programmable
- Remote reporting of takings and error messages
- Dimensions: height 450 mm, width 274 mm, depth 170 mm
- Weight: 9.0 kg
- Ambient conditions for operation: -5 °C to +45 °C
- Maximum humidity at +40 °C: 95%
- Handset with 775 mm cord
- A handset with 960 mm cord is optionally available

FMN communications GmbH
Grimmelallee 4
D-99734 Nordhausen
Phone: +49 (3631) 56-5000
Fax: +49 (3631) 56-3224
Email: info@fmn.de
Internet: www.fmncom.com